Title: SPECIFICATION FOR VITON VACUUM BAKEOUT

PREPARED BY:

NEGETIVIS'D

# SPECIFICATION FOR VITON VACUUM BAKEOUT

# LIGO VACUUM EQUIPMENT

Hanford, Washington and Livingston, Louisiana

JOB NO. V59049

QUALITY ASSURANCE:			ALAN BRADBOOK /RES						
TECHNICAL DIRECTOR:				D. a. mill illeans					
PROJ	JECT MANA	AGER:		Richard 1	Sagla	7			
					18				
						DEG 18 PAR			
MARTINI CONTRACTOR CON		The second secon		Account of the state of the sta			KINCOCO COMPONICIO CONTRACTO A CONTRACTOR A CONTR		
		ATO I AMERICAN PROPERTY OF THE STATE STATE STATE STATE STATE AND A STATE STATE OF THE STATE STATE OF THE STATE STA	OPENIO POSSIPPE PROVINCE PROVI	1 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -	(A) of Establish (A) is the second se		Plant - Amelika Hamiltoniani ya Kangdania Yaye anadar		
Property Commission also per principal and personal and p		The state of the s			er (d. del Bellegeneral Compa Col e manusco (n. 1644) que e	the second section of the second section section section sections and section section sections section sections.			
AND CHARLEST STORY OF SHIP SHAP AND ANALOGUE SEY SHIP SHIP	and the second s		NO PROGRAM SERVICE SER		Department of the second of th		E P. C.		
er erler his och läve kommission spater utspikken och statistik i tre statistik i med statis	Commencement the secondary continues the secondary of the	ACCUPATION OF THE PROPERTY OF		AND-FREE (FFFEE) (STATE SAME AND			according Sacring Street, in		
	Sin 12-11	246 DAW1	7.16.96 R	96 REV 1 RELEMBED PER DED 0386					
p.	Am 5/4/9	6 RE3	5/4/8 I	NITIAL RELEASE	OEO C	3/62	оом дост 2 — <del>2001 г</del> од — «Сентиский стору «Достиский высодия и медера (		
REVLTR	BY-DATE APPD, DATE			DESCRIPTION OF CHANGE					
PROC	ESS SYST	EMS INT	ERNATI	ONAL, INC.	and the state of t	SPECIFICA	TON		
INITIA APPROV	The second	PARED .	DATE 5/4/96	Approved DATE REAS 5	14/86	Number: A V049-2-1-22	Rev. /		
And the state of CO September 1	entra servicio de la companya de la	HAT MY THANK TO THE TOTAL TO THE STATE OF TH		adi kementan ya senemban ke ingani alian manasari alian ingan sana ang manasari kemendah ang k	a partie mestro establica e partie e	Page	Transport Of Sales		

## Title: SPECIFICATION FOR VITON VACUUM BAKEOUT

#### 1.0 PURPOSE

The purpose of this specification is to outline the procedure to be used to vacuum bake Viton O-rings for UHV service.

#### 2.0 GENERAL

This specification will be periodically updated as bakeout parameter data becomes available. Testing will be performed by PSI to develop a bakeout procedure that yields the best properties for Viton O-rings in UHV service, namely, low outgassing and high reliability.

#### 3.0 RESPONSIBILITY

It shall be the responsibility of the project engineer, PSI manufacturing, and QA personnel assigned to the Viton bakeout program to ensure that all procedures required by this specification are performed. Data sheets and test results for each lot of Viton that is processed will be signed and archived for future reference.

## 4.0 VITON BAKEOUT PROCEDURE

1. Prepare the following Viton bakeout system equipment for operation:

Vacuum oven

Vacuum pump

GN2 purge system

Instrumentation and controls

- 2. Load the Viton O-rings into the vacuum oven using clean room techniques to prevent contamination of the oven or Viton. *Log lot no., quanties and sizes.*
- 3. Close up oven.
- 4. Start rough pumping oven .Log time and ambient temperature.
- 5. Continue rough pumping until pressure reaches ~ 1 torr. Log time, oven pressure.
- 6. Start GN2 purge flow maintaining the oven pressure between 1 torr and 6 torr. It may be necessary to throttle the vacuum pump inlet valve.

SPECIFICATION							
Number:	A	V049-2-122	Rev.1				

### Title: SPECIFICATION FOR VITON VACUUM BAKEOUT

7. When oven pressure appears to have leveled off, start heating the oven. The temperature set point is 150.C. Log time, temp., oven pressure.

<u>Caution!</u> Dangerous byproducts may be formed if Viton is heated to a temperature greater than 200C

- 8. Once the temperature set point is achieved ,the goal is to maintain this temperature for 12 to 16 hours. Adjust the purge flow, as required, to maintain the oven pressure between 1 torr and 6 torr. It may be necessary to throttle the vacuum pump inlet valve.
- 9. Cooldown requires that the temperature is slowly ramped down at <u>30.C/hr</u>. The oven pressure may drop during cooldown. This is normal and requires no operator action. *Log time, set point, temperature, pressure every 2 hours*.
- 10. Cooldown is complete when the oven temperature is at ambient and the pressure has been stable for 1 hour. *Log* final readings when cooldown is complete.
- 11. Isolate oven and shutdown vacuum pumps.
- 12. Vent oven with GN2.
- 13. Vent vacuum pumps with GN2.
- 14. Shutdown purge flow system.
- 15. Remove Viton O-rings from the oven using clean room procedures. Visually inspect, bag and label the O-rings. Check and log the durometer of one O-ring from the batch. Note: after an O-ring has been baked, the suffix "V" in the O-ring part number must be deleted. This indicates that the O-ring is ready for vessel assembly.
- 16. Clean the vacuum oven in preparation for the next lot.

<u>Caution!</u> Deposits found in the oven or piping should be considered hazardous waste and must be handled and treated accordingly.

# **SPECIFICATION**

Number:

Rev.1

**A** V049-2-122

Title: SPECIFIC	ATION FOR	VITON VA	₹CUUM BAI	KEOUT			
	7	VITON BAK	EOUT DAT.	A SHEET		AMERICA AMERICA STATE OF THE ST	
Lot no Date By	Size Size Size		Quan Quan Quan	Durometer Durometer Durometer			
	1	2	3	4	5	6	7
Date/Time							
Operator							
Temperature							
Set Point		· · · · · · · · · · · · · · · · · · ·					
Oven		<u> </u>					
Pressure							
Purge Oven							
Pump							
T dillip							
Flow			OPPORTUGE AND COMPANY OF THE PROPERTY ASSESSMENT AND THE PROPERTY ASSESSMENT AND THE PROPERTY ASSESSMENT ASSES				kalandan menengga kalandan dan dengga di pangga di Sebanahan
Purge			TOTAL CONTROL OF THE PROPERTY				
Remarks							
							·
1							
				SPECIFICATION			
					Number:	V049-2-122	Rev.1