



DRILL AND TAP 2 HOLES
1/4-20 UNC 0.005"
OVERSIZE THRO'

PART NO.
SEE NOTE 4

DRILL AND TAP 2 HOLES
1/4-20 UNC 0.005"
OVERSIZE THRO' $\varnothing \varnothing 0.2$

NOTES: (UNLESS OTHERWISE SPECIFIED)

- REMOVE ALL SHARP EDGES, R.02 MIN.
- DO NOT SCALE FROM DRAWING.
- ALL MACHINING FLUIDS SHALL BE WATER SOLUBLE AND FREE OF SULFUR, CHLORINE AND SILICONE, SUCH AS CINCINNATI MILACRON'S CIMTECH 410 (STAINLESS STEEL)
- SCRIBE, ENGRAVE OR STAMP DRAWING PARTNUMBER ON NOTED SURFACE OF PART AND A THREE DIGIT SERIAL NUMBER. SERIAL NUMBERS START AT 001 FOR THE FIRST PART AND PROCEED CONSECUTIVELY. USE .07" HIGH CHARACTERS. EXAMPLE: D020188- 001. A VIBRATORY TOOL MAY BE USED.

DIMENSIONS ARE IN mm [INCHES]	
TOLERANCES:	
X.XX ±0.2 mm	
ANGULAR ±0.25 °	
MATERIAL: AL ALLOY 5083 OR SIMILAR	
FINISH: CLEAN AND DEGREASED	
$\sqrt{\mu m}$ [μin] Ra = 1.6	
NAME	DATE
DRAWN I WILMUT	14/Jun/07
CHECKED J'OD	--/--/--
APPROVED IW	--/--/--

CALIFORNIA INSTITUTE OF TECHNOLOGY MASSACHUSETTS INSTITUTE OF TECHNOLOGY 1GR, GLASGOW UNIVERSITY GEO 600 GROUP RUTHERFORD APPLETON LABORATORIES	
SYSTEM	ADVANCED LIGO
SUB-SYSTEM	SUS
NEXT ASSY	QUAD N-PTYPE WIRING HARNESS
PART NAME	WIRE CLAMP BODY (TOP RING WIRE CLAMP)
SIZE	B
DRG. NO.	D070215
SCALE	1:1
PROJECTION	
SHEET	1 OF 1