
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SINB CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF GNB CORPORATION IS PROHIBITED

REVISIONS REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	Α	REVISED WELD DETAIL, 72.75 WAS REFERENCE, 72.25 WAS NOT REFERENCE	7/14/2010	MKM2
	В	REVISED WELD PREP	8/11/2010	MKM2
	\Box	REVISED WELD PREP PER VENDOR CAPABILITIES	8/13/2010	MKM2
	D	RELEASED TO PRODUCTION	8/20/2010	MKM2




NOTES

SEAM TO ARRIVE WITH WELD PREPS IN PLACE.

- 2. TACK ROLL UP WITH CERTIFIED ROD ONLY (PROVIDED BY GNB).
- 3. CARBON STEEL ROLLERS SHALL BE COVERED WITH STAINLESS STEEL PRIOR TO ROLLING TO PREVENT CONTAMINATION.
- 4. SEAM EDGES SHALL BE PREWORKED TO ENSURE ROUNDNESS OF THE FINAL CYLINDER. 5. ROLL-UP PLATES MAY HAVE SHEARED EDGES ONLY IF THE SHEARED EDGES ARE THEN RE-CUT WITH A TUNGSTEN CARBIDE TOOL TO REMOVE CONTAMINATION BY THE ROLLING VENDOR. ACCEPTABLE CUTTING METHODS ARE PLASMA. LASER. WATER JET. OR CARBIDE CUTTING.
- FINAL BEVELS TO BE MADE WITH TUNGSTEN CARBIDE TOOLS ONLY.
- 7. PLATES AND ROLL-UPS MUST REMAIN PROTECTED FROM CONTACT WITH CARBON STEEL OR OTHER SOURCES OF CONTAMINATION DURING MOVING, WORKING, AND STORAGE. COVER CARBON STEEL WITH SST OR HEAVY PAPER, AND KEEP PLATES AND ROLL-UPS WRAPPED OR COVERED AT ALL TIMES WHEN NOT BEING PROCESSED. 8. A 2"X12" COUPON OF MATERIAL FROM THE SAME LOT OF MATERIAL MUST BE PROVIDED WITH EACH PIECE.
- ig(9.ig) ETCH THE HEAT/LOT NUMBER AND PART NUMBER WITH A VIBRATORY TOOL WITH MINIMUM TIP RADIUS OF .005"

DESCRIPTION: ROLL-UP, .250 WALL, 72.25 ID, 48.00 LG MATERIAL: AISI 304/ AISI 304L DUAL CERT PER SA240



SCALE 1:2

WELD PREP DETAIL

3

2