			<i></i>	PU	1/0	201	PU	7/ 3	SUM	MA	$\frac{RY}{}$	F OF	7 /	IIR	HA	ANL	)L1/	VG'	UN.	! /	4 <i>H</i> -	01					1E	MS.	<i>'</i>		·				
						1	NPUTS	; 								OUTF	บาร			ــــ			5	YSTEM	FEAT	URES					-				
	<u> </u>				LOG				4	В	INARY			DIG	ITAL		,	ANALO	XC		AL.	ARMS				PR	ROGRA	MS			1	GENER	PAL		
SYSTEM.	$\vdash$	ME	ASURE	0	+	CAL	CULA	TED	+				-	П	ТТ		<u> </u>	TET	ТТ	+	TT	ТТ	ТТ	+			ТТ	ТТ	$\neg \neg$		$\vdash$	ТТ	T 1	$\dashv$	
SYSTEM, APPARATUS, OR AREA POINT DESCRIPTION	TEMPERATURE	RH	KW AIR FLOW	LEVEL	VIBRATIONS	KWH ENTHAL PY	RUN TIME EFFICIENCY	WET BULB TEMP	STATUS	SMOKE	FREEZE AIR FLOW	METER	NO-130	OFF-AUTO-ON	OPEN-CLOSE	MULII-SIAGE	DAMPER POSITION VALVE POSITION	SET POINT ADJUSTMEN	SCR CONTROL	HI ANALOG	HI BINARY	PROOF		TIME SCHEDULING	DUTY CYCLE	START/STOP OPTION ENTHALPY OPTION	SMOKE CNT	ALARM INSTRUCT	MAINT WK ORD		COLOR GRAPHIC				SUPPLEMENTARY NOTES
OUTSIDE TEMERATURE	•	$\prod$	$\top$	$\top$	$\sqcap$	$\top$		TT	$\Pi$	$\Pi$			T	П	$\Pi$		П	П	$\prod$	П	П	TT	TT	$\prod$		T	П				П				
OUTSIDE RELATIVE HUMIDITY		•			$\sqcap$	$\top$		$\sqcap$	$\dagger \dagger$	$\top$	$\top$	$\top$	十		$\sqcap$			$\sqcap$	$\sqcap$	$\prod$	П	$\prod$	$\prod$	$\prod$		П	П		$\prod$	T	П	П		T	
PREHEAT COIL, HC-14	•	$\dagger \dagger$		$\top$	$\sqcap$	$\top$		$\sqcap$	0	$\dagger \dagger$	$\top$	$\forall$	$\top$	$\sqcap$	1	Ð	$\sqcap$	0	77	•	$\prod$	$\top$	$\top \top$	71	$\sqcap$	•	$\prod$	•	•	1	П	$\prod$	$\top \top$	T	
PREHEAT COIL, HC-15	•	11	$\top$	$\top$	$\dagger \dagger$	$\top \top$	$\top$	$\dagger \dagger$	0	11	$\forall$	$\dashv \dashv$	$\top$	$\sqcap$	1	9		•	$\top \!\!\!\! \top$	•	П	TT	11	T		•		•	9		П	$\prod$		T	
AIR FILTER AF-01 (TYP 2)			T	$\top$	$\dagger \dagger$	$\top$		$\dagger \dagger$	11	77	$\dagger \dagger$	$\top \top$	十	$\sqcap$	$\dagger \dagger$	T		$\sqcap$	$\top \!\!\!\! \top$	•	$\prod$	77	$\prod$	$\prod$	П		$\prod$	T	9	T			$\prod$		2 SENSORS
AIR FILTER AF-02 (TYP 2)	1		$\sqcap$	$\top$	$\sqcap$	$\dagger \dagger$	$\top$	$\sqcap$	$T^{\dagger}$	77	$\top \top$	$\dashv \dashv$	十	$\sqcap$	TT			$\sqcap$	$\top \top$	•	$\Pi \uparrow$	$\top \top$	$\prod$	$\prod$	$\prod$		$\prod$		9	T	$\prod$				2 SENSORS
MIXING AIR DAMPER OI		$\sqcap$	$\top$	$\top$	$\sqcap$	$\top$	$\top$	$\sqcap$	T	$\top \!$			$\top$	$\sqcap$	$\sqcap$		•	П	$\prod$	$\Pi$	П	$\prod$	$\prod$	П	$\prod$		П	•	•	П	П	П		T	
MIXING AIR DAMPER 02	$\exists \dagger$	11	$\top$	$\top$	$\sqcap$	$\top \dagger$		$\Pi$	11	$\dagger \dagger$			$\top$	$\sqcap$	$\sqcap$	$\top$	•	$\sqcap$	$\top \top$	TT	$\Pi$	TT	$\prod$	$\prod$			П	•	9	$\top$	П	1.		T	
COOLING COIL CC-01	•	$\Box$		1	$\dagger \dagger$	11	$\top$	$\Pi$	$\dagger \dagger$	11		$\top$	$\top$		TT		•	11	TT	•	П		$\prod$	$\prod$			F	•	•	Τ.	П	П	П	T	
COOLING COIL CC-02	•			$\top$	$\dagger \dagger$	$\sqcap$		$\prod$	TT	77	$\sqcap$	$\exists \exists$	T	П	П					•	П	П	П					•	•		П				
HUMIDIFIER HU-01		•		$\top$	$\sqcap$		T	П	•	$\sqcap$			T	П	T	Ð		•		0 0	I							•	•			-			
HUMIDIFIER HU-02	$\Box$		$\top$	$\top$	П	$\sqcap$	T	П	•	$\prod$	$\sqcap$	$\sqcap$	T	П	1	<b>D</b>		0	$\prod$	0 6								•	Ð						
SUPPLY FAN SF-01			•	$\top$	•		•	П	•	$\prod$	•		0		П			•		•		•		•		•		•	0						
SUPPLY FAN SF-02		П	•		0		•		•	П	•		•		П			•		•		•		•		•		•	9		Ш		Ш	$\perp$	
SUPPLY AIR TEMP (TYP 2)	•				П					П					П					0 0								0				$\coprod$		$\perp$	
SUPPLY AIR RELATIVE HUMIDITY		•																		0	$\coprod$	$\perp \perp$		$\perp \! \! \perp$	$\perp \downarrow$		Ш	•	Ш		Ш	Ш	Ш	$\perp$	
ROOM TEMPERATURE (TYPICAL 5 ZONES)	0																	Ш	Ш	0 0	11	$\bot\!\!\!\!\bot$	$\bot \bot$	11	$\perp \downarrow$		$\sqcup$	0			$oldsymbol{ol}}}}}}}}}}}}}}}}}}$		$\perp \downarrow$	$\perp$	
SPACE AVERAGE RELATIVE HUMIDITY		•				Ш				ot					Ш	Ш	$\perp$		$\perp \! \! \perp$	0 0	11	44	$\bot \bot$	$\bot\!\!\!\!\bot$	$\perp \downarrow$		$\sqcup$	•	$\perp \downarrow$	_	$\coprod$	$\bot\!\!\!\bot$	$\perp \downarrow$	1	
PONE DUCT HEATER (VEA)	•		$\perp \! \! \perp \! \! \perp$	$\perp$	Ш	$\perp \perp$	$\perp$	Ш	•	$\perp \downarrow$	$\perp \! \! \perp \! \! \! \perp$		$\perp$	Ш	$\coprod$	Ш	$\perp$	$\coprod$	0	0	11	44	44	$\bot\!\!\!\!\bot$	$\sqcup$	$\bot$	$\sqcup$	0		_		$\bot \downarrow$	$\downarrow \downarrow$	_	
PONE DUCT HEATERS (TYPICAL 5 ZONES)	0		$\perp \! \! \perp$	$\perp$	Ш	$\perp \perp$	$\perp$	Ш	•	Ш	$\perp \downarrow \downarrow$		$\perp$	Щ	•		$\perp$		$\bot\!\!\!\!\bot$	•	$\sqcup$	44	$\downarrow \downarrow$	$\bot\!\!\!\!\bot$	$\downarrow \downarrow$		$\sqcup$	0		_	$oxed{oxed}$	$\bot \bot$	$\bot\!\!\!\!\bot$	$\perp$	
MOKE DETECTOR (SD-01)			$\perp \! \! \perp \! \! \! \perp$			$\perp \downarrow$	$\perp$		Ш	•	Ш	$\perp \perp$	$\perp$		$\coprod$	Ц		$\coprod$	$\perp \perp$	11	$\coprod$	44	44	$\bot\!\!\!\!\bot$	$\bot \downarrow$		•	•	44	_		11	44	4	
AIXING AIR TEMP	0	1			Ш	Ш	$\perp$	Ш	$\coprod$	$\perp \! \! \perp$	$\perp \! \! \perp \! \! \! \perp$	$\perp \downarrow$	$\perp$		$\coprod$	$\perp \mid$	$\perp$		$\perp \! \! \perp$	$\coprod$	$\coprod$	44	$\bot \bot$	$\bot\!\!\!\!\bot$	$\downarrow \downarrow$		-	44	4	_	$oxed{\bot}$	$\downarrow \downarrow$	$\perp \downarrow$	4	
MIXING AIR RELATIVE HUMIDITY		•													Ш	Ш			$\bot \bot$	$\coprod$	$\sqcup$	$\bot \bot$	$\bot \bot$	$\bot \bot$	$\downarrow \downarrow$		$\coprod$	44	4	_	Ш	$\downarrow \downarrow$	$\perp \! \! \perp$	$\perp$	
IIR COMPRESSORS (TYP 2)	•	N .			$\coprod$			$\coprod$	•							ot				0 0	11	$\perp \perp$	11	$\bot\!\!\!\!\bot$	$\perp \mid$		$\sqcup \!\!\! \perp$	44	$\perp \downarrow$	$\perp$	Ш	$\perp \perp$	$\perp \perp$	$\perp$	
TOILET EXHAUST FAN, EF-01					Ш		•	$\coprod$	•				0								$\coprod$	•		0	Щ		$\coprod$	$\perp \perp$	•					1	
IIR FLOW DIAGRAM					Ш											Ш			11	$\perp \! \! \perp$	$\perp \perp$	$\perp \perp$	$\downarrow \downarrow$	$\bot\!\!\!\bot$	11		11	44	$\perp \! \! \perp$	$\perp$	•		$\perp \downarrow$	$\perp$	
IEPA FILTERS																				•	$\coprod$		$\bot \bot$	$\bot \!\!\! \bot$	$\perp \downarrow$	$\perp$	$\coprod$	$\perp \perp$	9		Ш	$\coprod$	$\perp \perp$	$\perp$	
LOOR PLANS	T	IT			IT	П	T	Π	IT		$\prod$		T		$\prod$							11									•				

		INPUTS		оитрит	TS .	S	YSTEM FEATURES	_]	
	ANALO	3	BINARY	DIGITAL	ANALOG	ALARMS	PROGRAMS	GENERAL	
	MEASURED	CALCULATED	DINAKI	DIGITAL	AMALOO	AEAIMO	1		
SYSTEM. APPARATUS, OR AREA POINT DESCRIPTION	TEMPERATURE RH KW KW AIR FLOW LEVEL COM	KWH ENTIALPY RUN TIME EFFICIENCY WET BULB TEMP	STATUS FILTER SMOKE FREEZE AIR FLOW METER	OFF-ON OFF-AUTO-ON OFF-HI-LO OPEN-CLOSE MALTI-STAGE	VANTER POSITION SET POINT ADJUSTMENT VANE POSITION SCR CONTROL	HI ANALOG LOW ANALOG HI BINARY LOW BINARY PROOF	TIME SCHEDULING DEMAND LIMITING DUTY CYCLE START/STOP OPTION ENTHALPY OPTION SMOKE CNT TREND ALARM INSTRUCT MAINT WK ORD	COLOR GRAPHIC	SUPPLEMENTARY NOTES
VATER CHILLER, CH-01	•   •	0	•	•		0 0			
WATER CHILLER, CH-02	• 6	•	•	•	•	• •			
CHILLED WATER PUMP, WP-01	0 0	•	•	•		• •			
CHILLED WATER PUMP, WP-02	• 6	•	•	•		• •			
CHILLED WATER RETURN TEMP	•								
CHILLED WATER SUPPLY TEMP	0								
CHILLED WATER BOOSTER PUMP	•	•	•	•					PUMP BY VE CONTRACTOR
CHILLED WATER FLOW DIAGRAM								•	
FLOOR PLANS								•	

## NOTES:

- 1. FOR LEGEND, ABBREVIATIONS AND GENERAL NOTES SEE SHEETS WA-H-001 AND WA-H-002.
- 2. SMOKE DETECTORS WILL BE HARD WIRED TO THE SUPPLY FANS SF-01 & SF-02 MOTOR STARTER TO STOP FANS WHEN SMOKE DETECTED IN THE RETURN AIR STREAM, ALSO SMOKE DETECTORS WILL BE SOFTWARE CONNECTED TO DDC CONTROL PANEL AND THE FACILITY CONTROL ROOM,
- CONTROL SYSTEM SHALL BE STAND ALONE TYPE AND CONNECTED TO THE MAIN CONTROL AND MONITORING SYSTEM AT THE FACILITY CONTROL ROOM IN THE CORNER STATION BUILDING.
- 4. VACUUM EQUIPMENT ROOM WILL BE PROVIDED WITH FOUR TEMPERATURE SENSORS TO CONTROL THE RESPECTIVE DUCT HEATER, SYSTEM MAY AVERAGE THE READING OF THE FOUR ROOM TEMPERATURE SENSORS OR SELECT ANY SENSOR TO CONTROL THE DUCT HEATER.

## SEQUENCE OF OPERATION:

- I. CHILLED WATER PLANT:
- UPON A SIGNAL FROM THE CENTRAL CONTROL SYSTEM THE PACKAGED CONTROLS PROVIDED WITH THE WATER CHILLER WILL PERFORM THE FOLLOWING:
- A. THE LEAD CHILLED WATER PUMP (MP-01) WILL START TO ESTABLISH STEADY WATER FLOW THROUGH THE SYSTEM.
- B. UPON PROOF OF ESTABLISHED WATER FLOW THE LEAD CHILLER (CH-01) WILL START TO MAINTAIN THE LEAVING CHILLED WATER TEMPERATURE SETPOINT (42°F).
- C. THE PACKAGED DOC CONTROLS ON THE WATER CHILLER WILL CYCLE THE REFRIGERATION COMPRESSORS IN SEQUENCE TO MATCH THE SYSTEM THERMAL LOAD.
- D. WHEN THE THERMAL LOAD DROPS BELOW THE MINIMUM OPERATING CAPACITY OF THE WATER CHILLER, THE PACKAGED CONTROL WILL ACTIVATE THE HOT GAS BYPASS CYCLE.
- E. PACKAGED CONTROLS WILL RUN SELF DIAGNOSTICS TEST BEFORE STARTING THE REFRIGERATION COMPRESSORS TO PROVE THAT ALL OPERATING CONDITIONS ARE WITHIN THE NORMAL LIMITS.
- F, PACKAGED CONTROLS WILL CONTINUOUSLY MONITOR THE CHILLER
  OPERATION AND REPORT ANY OPERATIONAL OR SAFETY ALARMS TO THE
  OPERATOR COMPUTER IN THE FACILITY CONTROL ROOM. PACKAGED
  CONTROLS WILL AUTOMATICALLY STOP THE MALFUNCTIONING WATER CHILLER
  AND START THE STANDBY CHILLER.
- G. CENTRAL CONTROL SYSTEM WILL ALTERNATE THE LEAD AND STANDBY WATER CHILLERS TO MAINTAIN EQUAL OPERATING PERIODS ON BOTH WATER CHILLERS.
- II. AIR HANDLING SYSTEM:
- UPON A SIGNAL FROM THE CENTRAL CONTROL SYSTEM THE LEAD SUPPLY AIR FAN (SF-01) WILL START TO ESTABLISH A STEADY AIR FLOW THROUGH THE SYSTEM. THE DDC CONTROLS WILL PERFORM THE FOLLWING:
- A. MODULATE THE CONTROLLABLE PITCH VANES ON THE SUPPLY AIR FANS TO MAINTAIN THE DESIRED CONSTANT AIR VOLUME FLOW RATE REGARDLESS OF THE SYSTEM STATIC PRESSURE.
- B. THE TEMPERATURE SENSORS LOCATED DOWN STREAM OF THE OUTSIDE AIR PREHEAT COILS WILL BE USED TO CONTROL THE CAPACITY OF THE DUCT ELECTRIC HEATERS TO MAINTAIN THE OUTSIDE AIR DRY BULB TEMPERATURE AT 50°F.
- C. THE TEMPERATURE SENSOR LOCATED DOWN STREAM OF THE COOLING COIL WILL BE USED TO MODULATE THE 3-WAY CONTROL VALVE ON THE CHILLED WATER LOOP TO MAINTAIN THE LEAVING AIR DRY BULB TEMPERATURE AT THE SET POINT (50°F).
- D. THE DOC CONTROLS WILL COMPARE THE SPACE ROOM TEMPERATURE SENSORS AND MODULATE THE FACE AND BYPASS DAMPER BASED ON THE MOST DEMANDING ZONE.
- E. THE ROOM TEMPERATURE SENSORS (TOTAL 4) OF VACUUM EQUIPMENT AREA SHALL BE USED TO MODULATE THE SCR CONTROLS ON THE RESPECTIVE ELECTRIC DUCT HEATER TO MAINTAIN THE ROOM TEMPERATURE SETPOINT (72°F)
- F. THE ROOM TEMPERATURE SENSORS FOR OTHER ROOMS SHALL BE USED TO SEOUENCE THE CAPACITY CONTROL STAGES OF THEIR RESPECTIVE DUCT HEATERS TO MAINTAIN THE ROOM TEMPERATURE SET POINT.
- G. WHEN THE ROOM TEMPERATURE RISES 5 DEGREES F ABOVE THE SETPOINT, THE CONTROL SYSTEM SHALL REPORT AN ALARM SIGNAL TO THE FACILITY CONTROL ROOM.
- H. THE RELATIVE HUMIDITY SENSOR LOCATED IN VACUUM EQUIPMENT ROOM SHALL BE USED TO SEQUENCE THE CAPACITY CONTROL STAGES OF THE ELECTRIC HUMIDIFIER TO MAINTAIN THE SPACE MINIMUM RELATIVE HUMIDITY SETPOINT (30 % RH).
- 1. THE SMOKE DUCT DETECTOR IN THE RETURN AIR DUCTS SHALL STOP THE SUPPLY AIR FANS WHEN SMOKE IS DETECTED IN THE RETURN AIR STREAM AND REPORT AN ALARM SIGNAL (AUDIO AND VISIUAL) AT THE FACILITY CONTROL ROOM AND LOCAL CONTROL PANEL.

  THE SPACE DIFFERENTIAL PRESSURE SENSORS SHALL BE USED TO MODULATE THE MOTORIZED CONTROL DAMPERS ON THE RETURN AIR DUCTS AND THE OUTSIDE AIR DUCTS TO MAINTAIN THE SPACE PRESSURIZATION AT THE SETPOINT.

## III. EOUIPMENT START UP:

- A. ALL WATER CHILLER SHALL BE SOFT START
- B. THE SUPPLY AIR FANS SF-01 & SF-02 SHALL START AT THE MINIMUM STATIC PRESSURE AND GRADUALLY INCREASE THE SYSTEM STATIC PRESSURE TO MAINTAIN THE DESIRED AIR FLOW RATE.
- C. THE BUILDING PRESSURIZATION SENSORS FOR LYEA AND OSB (LAB AREA) SHALL MODULATE THE MOTORIZED DAMPERS LOCATED ON THE RETURN AIR & OUTSIDE AIR DAMPERS TO START AT 100% RETURN AIR AND GRADUALLY MODULATE THE DAMPERS TO MAINTAIN THE BUILDING PRESSURIZATION SETPOINT.

## IV. TOILET EXHAUST FAN:

A. THE TOILET EXHAUST FAN WILL RUN CONTINUOUSLY.

OO WEST WALNUT STREET  CALIFORNIA INSTITUTE OF TECHNOLOGY MID & END STATIONS  MASSACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPERATION &  NA A SACHUSETTS INSTITUTE OF TECHNOLOGY SEQUENCES OF OPE	SKAL SIONS	DRAWN CLP CHECKED ENGINEER PROJ	PARSONS		LASER INTERFEROMETER GRAVITATIONAL-WAVE OBSERVATORY SITE NO. I - HANFORD, WASHINGT  HVAC MID & END STATIONS  HVAC NONE PP150969 8
PASAUENA, CALIFORNIA  I/O SUMMARY SHEET  I/O SUMMARY SHEET	DESCRIPTION NO. DATE BY CHIED FINE PROLI		100 WEST WALNUT STREET PASADENA, CALIFORNIA	MASSACHUSETTS INSTITUTE OF TECHNOLOGY	MID & END STATIONS SEQUENCES OF OPERATION & WA-H-231