


SECTION A-A



SECTION B-B

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES

TOLERANCES:
FRACTIONAL \pm
ANGULAR $\pm 5^\circ$
ANGULARMACH \pm BEND \pm
TWO PLACE DECIMAL $\pm .03$

THREE PLACE DECIMAL $\pm .005$
FINISHED SURFACE 32 MICRINCH AVERAGE
BREAK CORNERS IN: OUT: .005-.010
REMOVE ALL BURRS

MATERIAL:
TEFLON PFA 440 HP

HEAT TREAT:

FINISH:

USED ON:

NEXT ASS'Y: D961444/D961445

REV	DESCRIPTION	DCC	SYS	DET	CDS	VE	CC	BT	CHECK	DRWN	DATE
A	DCN E960157										
01	RELEASE FOR FAB										
0A	PRELIMINARY RELEASE										
00	PRE-RELEASE									CONLEY	10-29-96

LIGO CALIFORNIA INSTITUTE OF TECHNOLOGY
MASSACHUSETTS INSTITUTE OF TECHNOLOGY

CORE OPTIC COMPONENT CARRIER
SIDE PAD

CAD FILE
D961423-A.dwg

SIZE DWG. NO.
A D961423-A-D

SCALE
NTS

SHEET
1 OF 1

ISSUE DESCRIPTION