



SUPPORT FROM GATE VALVE USING MODIFIED FIN CLAMP PER DWG V049-4-163, & DETAIL 'B' ON DWG V049-4-109 (BY FIELD CONTRACTOR) (2 REQ'D)
SEE FIELD BOM V0491151G1 FOR CLAMPS TO GATE VALVE, BY PSI.

- NOTES**
- 1) WASHINGTON - QUANTITY (2)
USED WITH DWG. DV049-4-165
ANNULUS TUBING & 25 TON PUMP
 - 2) NO BRAID ON FLEX HOSES.

MATERIAL: 304 STAINLESS STEEL

INSTALL LIKE THIS.

PROPRIETARY AND CONFIDENTIAL
THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION BELONGING TO PROCESS SYSTEMS INTERNATIONAL, INC. OR ITS AFFILIATED COMPANIES AND SHALL BE USED ONLY FOR THE PURPOSES FOR WHICH IT WAS SUPPLIED. IT SHALL NOT BE COPIED, REPRODUCED OR OTHERWISE USED IN ANY MANNER WITHOUT THE WRITTEN CONSENT OF PROCESS SYSTEMS INTERNATIONAL, INC. AND SHALL BE RETURNED UPON REQUEST.

REV.	DESCRIPTION	DATE	BY	CHKD	APP'D
1	ISSUED FOR FABRICATION / BIDS	11/21/96	GW	GW	GW
2	REISSUED FOR CONSTRUCTION	6/5/97	GW	GW	GW

LIGO-D970415-01-V

PROCESS SYSTEMS INTERNATIONAL, INC.
25 ANNULUS TUBING ISO
48" GATE VALVE
TYPE I

SCALE: 1" = 1'-0"

SHEET: 1 OF 1

OCT 25, 1996 - 08:40:23