
Summary of LHO Vacuum Bake Oven A RGA Data Generation

The individual parts which comprise a "load" are cleaned as per LIGO-E960022 or as allowed by waiver(s) and loaded into the bake oven. The oven is then pumped down through the main pump "arm" (through V-2, RGA arm is valved off at this point). A heating profile is programmed and baking of the system begins. A typical "heating profile" consists of ramping up to material type soak temperature, soaking for approximately 48 hours, ramping down to approximately 70C, soaking and then ramping down to near room temperature. While soaking at 70C, an RGA background scan is taken. V-1 is then opened and V-2 closed. Enough time is allowed for the system to come into pressure equilibrium and then an elevated load temperature RGA scan is taken. V-1 is then closed and V-2 opened. Following this elevated temperature scan, the load is ramped down to near room temperature and the baking portion of the process is complete. Throughout the baking, temperature data is taken to verify the actual temperatures in the various "heat zones" of the bake oven system.

Once at near room temperature, another RGA background (V-1 closed) scan is taken. Next, V-1 and the cal-gas are opened and V-2 closed. After a 30 minute pressure equilibration time, a "calibration" scan is taken. The calculated pressure of Argon (constituent of the "mixed" calibration gas) is determined using the leak rate of Argon and the pump speed of the RGA arm port as seen by the oven chamber and compared (ratio) to the maximum amp value measured for Argon in the calibration scan. This "torr/amp" ratio becomes the Calibration Factor for the given load, converting measured current to pressure.

Finally, the cal-gas is valved out and enough time is allotted to allow all traces of it to be pumped away. A "post-bake" scan is then taken. Approval of the post-bake scan is a collective "pass/fail" determination made by either Dennis Coyne (CalTech) or Stan Whitcomb (CalTech). The data collected during the "elevated temperature scan" is entered into a spreadsheet which then calculates what the outgassing rates of AMUs 41, 43, 53, 55 and 57 ought to be at room temperature. These calculations are used to determine the room temperature outgassing rates when the signals are below the RGA's sensitivity (noise floor).

Refer to the LHO Vacuum Bake Oven A logbook for the actual ordered events of the load # of interest.



LHO VACUUM BAKE OVEN A: CONTENTS LOAD #70

BEAM DUMP ASSEMBLIES, BSC4

BEAM DUMP FLEX HINGE CLEVIS SERIAL NUMBER D990029-A-011

B.S.C. ISOLATION STACK LEG ASSEMBLY PINS AND SCREWS

B.S.C. LEG SCREW SERIAL NUMBER D972717-D-1 (24ea)


B.S.C. LEG SCREW SERIAL NUMBER D972717-D-3 (24ea)

B.S.C. LEG SCREW SERIAL NUMBER D972717-D-5 (24ea)


B.S.C. SAFETY PIN SERIAL NUMBER D972717-D-9 (24ea)

MISC. SS NOZZLES SERIAL NUMBER N/A (3ea)

LHO VACUUM BAKE OVEN A LOAD 70



LHO VACUUM BAKE OVEN LOAD 70 REBAKE




LHO VACUUM BAKE OVEN A LOAD #70 ELEVATED TEMPERATURE BACKGROUND SCAN

V-1 Closed

NO ELEVATED BACKGROUND SCAN AVAILABLE

LHO VACUUM BAKE OVEN A LOAD #70 ELEVATED TEMPERATURE SCAN

V-1 Open, Cal-Gas and V-2 Closed, 70°C




LHO Bake Oven A Load # 70

$\mathbf{1^{st}\ Order\ Desorption\ Outgassing\ Rate\ Estimates\ using\ Q_{low} = SP_{low} = SP_{high}[e^{(E_s/kT_{high})}]/[e^{(E_s/kT_{low})]}$

| Number of nits in bake load | Pump Speed (L/sec) | AMU | RGA background current (amps) | RGA current (amps) @ High Temp | Calibration Factor CF (torr/amps) | High Temp (K) | Low Temp (K) | Es/k | Extrapolated outgassing rate (torr*L/sec) @ T _{low} |
|-----------------------------------|-----------------------|-----|--|--------------------------------------|--------------------------------------|---------------|--------------|-------|--|
| 1 | 5 | 41 | no scan | 7.90E-19 | 1.00E+07 | 3.43E+02 | 2.96E+02 | 13000 | #VALUEI |
| 1 | 5 | 43 | no scan | 3.14E-18 | 1.00E+07 | 3.43E+02 | 2.96E+02 | 8000 | #VALUE! |
| 1 | 5 | 53 | no scan | 7.80E-20 | 1.00E+07 | 3.43E+02 | 2.96E+02 | 13000 | #VALUE! |
| 1, | 5 | 55 | no scan | 2.60E-19 | 1.00E+07 | 3.43E+02 | 2.96E+02 | 15000 | #VALUE! |
| 1 | 5 | 57 | no scan | 1.50E-19 | 1.00E+07 | 3.43E+02 | 2.96E+02 | 15000 | #VALUEI |


LHO Vacuum Bake Oven A Load #70 RGA Background

V-1 closed, room temperature



LHO Vacuum Bake Oven A Load #70 Post-Bake Scan Room Temp.

V-1 open, Cal-Gas and V-2 Closed



E990445-30-★
DCC Number: E98____-00-X

Date Prepared: \[\bar{2} \cdot (5 \cdot 97) \]

| Orlginator | | Cogniza | nt Engineer | Ext/Phone | Project | Account Number |
|--|------------------|--|----------------------------------|--|--|-------------------|
| BRIVERA | 1771 | くえ アル | | F088X | man de la companie d | 5F5 11 |
| Dwg/Part Number | Rev | Armount to a letter professional Asian a representative research | art Description | A Committee of the Comm | Serial Number | Qty |
| 154-2-17 - 1 | 13°SC 3 | 2 40114105 EC SUSLU IG 47574 | 10.6 15C #52 21014 11.45 | Selection and the second | · 建进程的企业。2010年19日,19日本 | 24 24 24 |
| Used In (next higher assembly); | | | | | ı | <u> </u> |
| | Yendor Nam | e in the second | | | /Contract Number | |
| Data Package, Receiving/Inspect | ion Domeoules: | | | P | | |
| Inspection Visual Required Y/N Damage Y/N | | | Conments . | | Name/ Linidals | Date Comp. |
| YES NO | HINOR CHI | PPING AND | WEAR OF SIVER | SIATINC, | B.ROSRA | 12.13.9q |
| Process Flow: # Operation | Start Date | York Area | Tosi cus | tions 27 m | Name/ Initials | Date Comp. |
| Clean & Vacuum Bake per LIGO Vacuum Prep. Form | 121599 | HO po | er E960022-A | e e a constante la presentación de la constante de la constant | BRUFILA | 1 |
| 2 Control Point | | IA R | eview/approve RGA scan ムムの 干る | #122399 C. RGF | - K11 | 1/4/00 |
| 3 Wrap & Tag vacuum clean parts per E960022-A | C | CIT | per package | | TV W | 1,7,00 |
| 4 | | EIT N | lote: Copy this trayeler a | nd give to the DCC | | |
| END: Go to Traveler associated w | vith next higher | assembly proc | essing | | | |

| ions (Handling/Pac | | 5 | | 71 Hotes, | <u>,, , , , , , , , , , , , , , , , , , ,</u> | | | | |
|--------------------|-------------|-------|-----|---------------|---|-------------|--------------|-------------|-------------|
| | | | | | <u> </u> | | - | | |
| | | . • . | • . | | | | | | |
| | | | | | <u> </u> | | | | |
| | | | | | | | | | |

DCC Number: E98 -00-X

Date Prepared:

| Dyg/Part Number Revit Part Sept S | Originator | The second | izant Digineer Three | | Project (1) | Account Number |
|--|--------------------------------|--|--|--|---|--|
| Dwg/Part Number Rev. Manusc. So. Notes Notes Notes Number | BRIVERE | びででんし | TEMESTAL AND THE PROPERTY OF THE PERSON AND THE PER | SIGI | · 位于 医二十二 | 4 (1977) |
| Used In (next higher assembly) is Used In (next higher assembly) is | Dwg/Part Number | Revitalist | PATE DESCUEIDANTERS PROPERTY | MANAGE SELECTION | Number | Qly |
| Pata Package, Receiving/Inspection Remarks: Inspection Visual Required Y/N Damage V/N | NIG | MA Misc 55 | NO73125 | NIC | differ to display the Display and | 3 |
| Data Package, Receiving/Inspection Remarks: Inspection Required Y/N Damings VN Process Flow: # Operation Start Date Comp. Clean & Vacuum Bake per LIGO Vacuum Prep. Form CPT per E960022-A Control Point NA Review/approve RGA scan #122592.RCA 1/4/68 Wrap & Tag vacuum clean parts per E960022-A CIT Note: Copy this traveler and give to the DCC Note DCC Note Copy this traveler and give to the DCC Note DCC Note Copy this traveler and give to the DCC No | Used In (next higher assembly | | | | | |
| Data Package, Receiving/Inspection Remarks: Inspection Required Y/N Damings VN Process Flow: # Operation Start Date Comp. Clean & Vacuum Bake per LIGO Vacuum Prep. Form CPT per E960022-A Control Point NA Review/approve RGA scan #122592.RCA 1/4/68 Wrap & Tag vacuum clean parts per E960022-A CIT Note: Copy this traveler and give to the DCC Note DCC Note Copy this traveler and give to the DCC Note DCC Note Copy this traveler and give to the DCC No | | The state of the s | | | | **** |
| Data Package, Receiving/Inspection Remarks: Inspection Required Y/N Damings VN Process Flow: # Operation Start Date Comp. Clean & Vacuum Bake per LIGO Vacuum Prep. Form CPT per E960022-A Control Point NA Review/approve RGA scan #122592.RCA 1/4/68 Wrap & Tag vacuum clean parts per E960022-A CIT Note: Copy this traveler and give to the DCC Note DCC Note Copy this traveler and give to the DCC Note DCC Note Copy this traveler and give to the DCC No | | Yellor Name Harris | | WANTED TO/Conf. | inct Number | |
| Inspection Planning Process Flow: | D-4- Balla B | | P | And the state of t | splanting a state of all sales of a free of the sales | |
| Required Y/N Domage Y/N Process Flow: # Operation Stort Dote Area Comp. Clean & Vacuum Bake per LIGO Vacuum Prep. Form Clean & Vacuum P | | | S MA MARINE AS SAME. | | | |
| Process Flow: # Operation Start Date Area Per LIGO Vacuum Bake per LIGO Vacuum Prep. Form 2 Control Point NA Review/approve RGA scan #122 99 C.RUS 12389 3 Wrap & Tag vacuum clean parts per E960022-A CIT Note: Copy this traveler and give to the DCC | | | A Comments & Comments | | Name/ Vinitials | Date Comb |
| # Operation Stort Dole 13 Teb 12 Teb 12 Teb 13 Teb 13 Teb 13 Teb 13 Teb 14 Teb 13 Teb 14 Teb 14 Teb 15 Teb 15 Teb 15 Teb 15 Teb 15 Teb 16 Teb 16 Teb 16 Teb 16 Teb 17 Teb 17 Teb 17 Teb 18 Teb | Process Flow | # 1 #RT | 等等的人类社会。如何的企业的人类主义的《经验》中的人工工。企业的实验中的生活。 | | RUERA | 11 12 13 13 13 13 13 13 13 13 13 13 13 13 13 |
| Clean & Vacuum Bake per LIGO Vacuum Prep. Form LIGO Vacuum Prep. Form LIGO Vacuum Prep. Form LIGO Vacuum Prep. Form NA Review/approve RGA scan #1225990.RCA Load #70 1/4/co | # Operation | Stort Dates of Area w | | | (t. Naine) Initials | Date : Comp. |
| Review/approve RGA scan #122599C./CC Wrap & Tag vacuum clean parts per E960022-A CIT Note: Copy this traveler and give to the DCC Parts P | LIGO Vacuum Prep. Form | | per E960022-A | | 30NEOD | 4 |
| Wrap & Tag vacuum clean CV | | NA NA | Review/approve RGA scan #15 | 125990.Rh | 15/1) | 1/4/0 |
| CIT Note: Copy this traveler and give to the DCC | | | | | ACW | - / · / · · · · · · · · · · · · · · · · |
| END: Go to Traveler associated with next higher assembly processing | 4 | CIT | Note: Copy this traveler and | give to the DCC | 1 1/1 | |
| | END: Go to Traveler associated | with next higher assembly p | rocessing | No. 10 | | i diki h |

N.B.: A copy of this traveler must be submitted to the DCC each time the original is shipped with the associated part(s) and when the traveler has been completed.

| LIGO PROCESS | TRAVELER | | | GOOGOST 00 -X |
|--------------------------|----------------------------|-----------------------------|--------|-----------------------------|
| Transfer sections (FIAI) | dling/Packaging Constraint | s, Remarks, etc.) or Notes: | DCC No | Imber: E9800-X _ |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

DCC Number: **E990267-01-X**

Date Prepared:

6/30/99

| C | Originat | or Cognizant Engineer | | Ext./I | Phone# | | Proje | ect | Acco Num | | | | |
|--------------------|----------|---|---------------------------------|--------|----------------------------|-----------------------|--|----------------------------|----------------------|-------------------|---|--|--|
| Michael Smith | | Michael Smith | 206 | 52 | | | COS | | 5F515 | | 1 | | |
| Dwg/Part Number | Rev | Part Description | Serial Number | Qty | VBO load 40 6/ 28 | VBO lond 41 7/1 | VBO load 43 7/ 12 | VBO load 46 7/ 26 | VBO load 48 7/ | VBO Load 50 | \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ | | |
| | | Beam Dump Assemblies, BSC4 | | | | | | | | | - | | |
| 0980087 | Α | "glass retaining bracket, top left, cavity BD" | 006-008 | 3 | 3 | | 3 | | | | - | | |
| 980088 | A | "glass retaining bracket, top right, cavity BD" | 006-008 | 3 | 3 | | 3 | } | | | - | | |
| 980092 | A | "glass plate 1, cavity BD" | | 3 | | | | | | | - ` | | |
| 980093 | A | "glass plate 2, cavity BD" | | 3 | <u> </u> | <u> </u> | | | | | - | | |
| 980289 | В | "glass mounting plate1, cavity BD" | 006-008 | 3 | 3 | 1 | | | | | - | | |
| 980292 | В | "glass mounting plate2, cavity BD" | 007,008,015 | 3 | 2 | | 1 | 1 | | | - | | |
| 980296 | A | "glass retaining bracket, bottom left, cavity BD" | 006-008 | 3 | 3 | | 3 | | | | | | |
| 980297 | A | "glass retaining bracket, bottom right cavity BD" | 006-008 | 3 | 3 | | 3 | | | | _ | | |
| 980348 | В | "side plate, cavity BD" | 012-017 | 6 | 5 | 1 | |) | | | _ | | |
| 980378 | В | "Stiffener Block, cavity BD" | 006-008 | 3 | 3 | | - | | | | - | | |
| 980685 | A | "clamp, plate beam dump" | | 12 | | 1. | | | | | - | | |
| 990028 | A | Beam Dump Flex Hinge Tongue | 004, 005, 006, 007, 010, 015 | 6 | 1 | 3 | 2 | 2 | | | - | | |
| 990029 | A | Beam Dump Flex Hinge Clevis | 005, 008-012 | 6 | 1 | | 1 | 5 | | (011) | - | | |
| 990030 | A | Beam Dump Flex Hinge Tee | 005-010 | 6 | 6 | | | 6 | Ï | | <u>-</u> | | |
| 990031 | A | Beam Dump Flex Hinge Saddle | 004-009 | 6 | | 4 | | 2 | | | _ | | |
| 990032 | A | Beam Dump Flex Hinge Attach | 004-006, 009- 011 | 6 | | 4 | | 2 | | | _ | | |
| 990033 | A | Beam Dump Flex Hinge Adapter | 004, 005, 008- 010, 014 | 6 | | 6 | | | | | _ | | |
| 990140 | D | Beam Dump Housing Plate | 012, 014 | 3 | | | | 3 | | | _ | | |
| 990149 | C | "Cavity Beam Dump, Mounting Bracket Angle " | 005-008 | 4 | 1 | | | 3 | | | _ | | |
| 990150 | В | "Cavity Beam Dump, Mounting Bracket Gusset " | 005-008 | 4 | 4 | | | | | | - | | |

N.B.: A copy of this traveler must be submitted to the DCC each time the original is shipped with the associated part(s) and when the traveler has been completed.

DCC Number: **E990267-01-X**

| Dwg/Part Number | Rev | Part Description | Serial Number | Qty | VBO load 40 6/ 28 | VBO load 41 7/1 | VBO load 43 7/ 12 | VBO load 46 7/ 26 | VBO load 48 7/ | VBO Load 50 5 |
|--------------------|---------------------------------------|--|-------------------------------|-----|----------------------------|-----------------------|---------------------------------------|----------------------------|----------------------|--|
| D990151 | В | "Cavity Beam Dump, Mounting Bracket Backplate 1" | 005-008 | 4 | 4 | | · · · · · · · · · · · · · · · · · · · | | | |
| D990152 | C | "Cavity Beam Dump, Mounting Bracket Backplate 2" | 005-008 | 4 | 4 | | | | | ····· |
| D990198 | В | Beam Dump Flex Hinge H_tube | 007,0(0,005 | 4 | 1 | 2 | | | 1 | · · · · · · · · · · · · · · · · · · · |
| D990199 | Α | Beam Dump Flex Hinge Low Strap | 004-009 | 6 | 1 | 5 | | | | ···· |
| D990200 | A | Beam Dump Flex Hinge Backup | 016-018, 020- 022, 010-015 | 12 | 2 | 10 | | | | |
| D990201 | A | Beam Dump Flex Hinge Cap | 007-017, 019 | 12 | 2 | 2 | | 8 | | |
| D990202 | В | Beam Dump Flex Hinge Top Strap | 005-010 | 6 | 1 | 4 | | 1 | | |
| D990207 | В | "rail, plate beam dump" | 003-006, 008, 009 | 6 | | 6 | | | | |
| D990218 | В | "glass, plate beam dump" other traveler | NA | 3 | | | 3 | 3 | | |
| D990222 | A | Beam Dump Housing Tube 2KBSAR3 | | 0 | | | | | <u> </u> | |
| D990223 | C | Beam Dump Housing Tube 2KFM | | 0 | 1 | | | | | - : |
| D990225 | D | "Beam Dump Housing Tube 4KITMHR3,4KITMHR4" | | 0 | | | <u> </u> | | | |
| D990236 | В | "backplate_offset, plate beam dump" | | 0 | | | | | | |
| D990240 | В | "backplate, plate beam dump" | | 2 | 1 | <u> </u> | | | | |
| D990252 | В | "Beam Dump Housing Tube ITMAR1,2KRMHR3" | 001,005,007 | 3 | 1 | 2 | . 1 | | | ٠ - |
| D990253 | A | Extension Tube | 003 | 1 | | | 1 | | 1 | |
| D990335 | A | "Beam Dump Flex Hinge H_tube, 2KITMXAR4 " И | 001 | 1 | 1 | | 1 | | 1 | |
| D990336 | Α | "Beam Dump Flex Hinge H_tube, 2KITMYAR4" | 002 | 1 | | | 1 | | 1 | |
| WFV-10 | | #10 X 0.31 THK FLAT VENTED WASHER | | 24 | 24 | <u> </u> | | | | |
| WFV-10 | | #10 X 0.31 THK FLAT VENTED WASHER | | 4 | 4 | 1 | | · | | |
| 92196A245 | · · · · · · · · · · · · · · · · · · · | #10-24 X 0.75 SHCS | | 4 | 4 | <u> </u> | , | | | |
| 93615A355 | | #10-24 X 0.75 LOW HD SCS | | 24 | 24 | | | | | |
| WFV-06 | - | #6 X 0.016 THK FLAT VENTED WASHER | : | 4 | 4 | | <u> </u> | | | |
| 92196A144 | 1 | #6-32 X .25 SHCS | | 4 | 4 | | | | | |
| WFV-08 | | #8 FLAT VENTED WASHER | | 102 | 102 | | | | | |

DCC Number: E990267-01-X

| Dwg/Part Number | Rev | Part Description | Serial Number | Qty' | VBO load 40 6/ 28 | VBO Joad 41 7/1 | VBO load 43 7/ 12 | VBO load 46 7/ 26 | VBO lond 487/5 |
|-----------------|--------------|---|------------------|------|----------------------------|--|----------------------------|--|----------------------|
| 92185A194 | | #8-32 X .50 SHCS | | 102 | 102 | <u> </u> | | | |
| 91500A194 | | #8-32 X .500 FHPS | · · | 54 | 54 | <u> </u> | | | |
| 91944A450 | <u> </u> | 0.406ID X 0.88OD X 0.25 THK SPHER WASH | | 24 | 24 | | | | |
| 92141A029 | | 1/4 FLAT WASHER | | 48 | 48 | | | - | |
| 92141A029 | | 1/4 FLAT WASHER | | 36 | 36 | | | | |
| N-2520-A | | 1/4-20 HEX NUT | | 24 | 24 | | | | |
| 93615A410 | - | 1/4-20 X .500 LOW HEAD SOCKET SCREW | | 12 | 12 | | | | |
| 92196A540 | | 1/4-20 X 0.75 SHCS | | 48 | 48 | | | | |
| 92196A540 | | 1/4-20 X 0.75 SHCS | | 24 | 24 | | | | |
| 92196A542 | | 1/4-20 X 1.00 SHCS | | 48 | 48 | | | | |
| C-2016-NA | | "1/4-20 X 1.00 SHCS, AG/SS" | | 48 | 48 | | | | |
| C-2016-NA | | "1/4-20 X 1.00 SHCS, AG/SS" | | 12 | 12 | | | | |
| 92196A544 | | 1/4-20 X 1.25 SHCS | | 24 | 24 | | | | |
| C-2820-NA | | "1/4-28 X 1.25 SHCS, AG/SS" | | 36 | 36 | | | | ····· |
| 91950A031 | | 3/8 X 0.063 FLAT WASHER | | 3 | 3 | | | | |
| 91950A031 | | 3/8 X 0.063 FLAT WASHER | <u> </u> | 6 | 6 | | | | |
| WFV-38 | | 3/8 X0.032 THK FLAT VENTED WASHER | | 3 | 3 | | | | |
| WFV-38 | | 3/8 X0.032 THK FLAT VENTED WASHER | | 32 | 32 | <u> </u> | | | |
| WFV-38 | | 3/8 X0.032 THK FLAT VENTED WASHER | | 8 | 8 | | | | |
| 94804A320 | ······ | 3/8-16 HEX NUT | | 8 | 8 | | | | |
| N-3816-A | | 3/8-16 HEX NUT | | 6 | 6 | | | | |
| TOP-1616-NA | | 3/8-16 X 1.00 SOCKT SET SCRW-OVL PT AG/SS | | 12 | 12 | | | | |
| 90585A626 | | 3/8-16 X 1.25 FLT HD CAP SCREW | | 8 | 8 | ų. | | | |
| 92186A626 | | 3/8-16 X 1.25 HEX HD SCREW | | 16 | 16 | | <u> </u> | | |
| C-1620-NA | | "3/8-16 X 1.25 SHCS, AG/SS" | | 12 | 12 | | | | |
| 92186A630 | | 3/8-16 X 1.75 HEX HD SCREW | 1 1 | 6 | 6 | | | | |

DCC Number:

E990267-01-X

Date Prepared:

6/30/99

| Dwg/Part Number | Rev | Part Description | Serial Number | Qty | VBO load 40 6/ 28 | VBO load 41 7/1 | VBO load 43 7/ 12 | VBO load 46 7/ 26 | VBO load 48 7/ |
|---------------------|---------|---|------------------|-----|----------------------------|--|---------------------------------------|--|----------------------|
| 92196A630 | | 3/8-16 X 1.75 SHCS | <u> </u> | 18 | 18 | Γ | · · · · · · · · · · · · · · · · · · · | | |
| 92186A999 | | 3/8-16 X 7.00 HEX HD SCREW | | 16 | 16 | | | | |
| 099-966-12-20x | | BERYLLIUM-CU GND STRP | | 12 | 12 | | | | |
| 6.32-400 | | Flex Pivot | | 12 | 12 | | | | |
| Used In (next highe | r assen | ably): D990230, BSC Beam dump Installation, top ass | sembly | | | <u> </u> | | | <u> </u> |
| 4 | | | T | | | <u> </u> | | | |

Data Package, Receiving/Inspection Remarks:

Inspection Required Y/N

Visual Damage Y/N

Comments

Name/ Initials

Date Comp.

Inspect for breakage during shipment

Process Flow:

| # | Operation | Start Date | Work Area | Instructions | Name/ Initials | Date Comp. |
|----|---------------|---|-----------|------------------------------------|-------------------|-------------------------------|
| 1. | Control Point | NA | NA | | NA | NA |
| 2 | Clean | | LHO | per LIGO-E960022, as applicable | B. Weaver | |
| 3 | Vacuum Bake | | LHO | per LIGO-E960022 3 (N ER | K. Ryan | |
| 4 | wrap and bag | | LHO | per LIGO-E960022 | B. Weaver | |
| 5 | Control Point | C/24/99 6/28/99 7/6/99 7/20/99 | LHO | Review/approve RGA: VBO Load# 40 | SEW SEW SCL | 7/28/99 8/10/99 8/10/99 |

N.B.: A copy of this traveler must be submitted to the DCC each time the original is shipped with the associated part(s) and when the traveler has been completed.

VBCLORD TO SCOWE 122399C. (CA

LIGO Form traveler-03 (10/16/98)

DCC Number: <u>E990267-01-X</u>

Date Prepared: 6/30/99

| # | Operation | Start I | Date W | ork Area | | | Instructions | Name/ Initials | Date Comp. |
|---|-------------------------------|---------------------------------------|-------------|--------------|----------------|--------------------|--|-------------------|---------------|
| | Box for shipment to LHO | | | < c | Ship in | LIGO-provi | ded container | | |
| | | | | | No. | Qty per package | Part | | |
| | | | | | ALL | | BSC4 BEAM DUMP PARTS | | |
| | | | | | | | | | |
| | | | | | 1. | | | | |
| | | | | , | (see als | o qty. for ea | ch shipping destination below) | | |
| 7 | Ship | | | | <u> </u> | . <u>.</u> | | | |
| | | | | Ship Qt | y. | | _ | | |
| | | No. | LHO | LLO | Othe | er | Part Description | | |
| | | | all | | | BSC4 | beam dump parts | | |
| | | · · · · · · · · · · · · · · · · · · · | LH | O: | LIGO F | | COS ervatory (LHO) eam dump BSC8 | | |
| | | | LL | O: | LIGO I | | bservatory (LLO) cam dump BSC8 | - | ٠. |
| E | ND: Go to Traveler associated | L ciated with | th next hig | her assemb | l ly proces | sing | | | |
| | | · · · · · · · · · · · · · · · · · · · | | | <u> </u> | | | | |

N.B.: A copy of this traveler must be submitted to the DCC each time the original is shipped with the associated part(s) and when the traveler has been completed.

DCC Number: <u>E990267-01-X</u>

Date Prepared:

6/30/99

| Special instructions (Handling/Packaging Constraints, Remarks, etc.) or Notes: |
|---|
| Attention: Betsy Weaver, Jonathan Kern, hold cleaned and baked parts for COS assembly |
| VBO Load 43 - Rejected Scan. Dennis Coyne sent all stainless steel items to be electropolished and all aluminum items to LNL anodizing to be etched, from this load. 7/15 B. Weaver |
| Parts received back from etching and polishing companies. Recleaned as per Dennis' email attached. 7/23 B. Weaver |
| S/N 006-008 of parts D980087, D980088, D980296, D980297 sent back to Spacecraft Specialists, Inc. for rework. They were rushed during manufacturing these parts, and therefore forgot to finish. 7/21 B. Weaver |
| they had been botted at Litto of passed. Donnis throught they looked suspect to dist. |
| UMS 1990029-011 Sent out for remark to make modification as per D990029-8 |
| 8/4-B. Wesver DCV: E990273-B 7/9 |
| Side plate 1980348 sh 014 Sent to Brockman Mfg. for remork - holes made into slots to compensate for low chearance. B. Wesver 9/10 |
| D900348 slh 014 given to B. Rivera for vacuum baking. B. Wesver 10/11 |
| clevis D990029 s/nor sent out Agrin to have 14-20 tapped holes retapped. 12/1/99 B.Wesner |
| Received clevis D990029 5/n 011 back from Brockman-Veworking about Giving to B. Rivers for redesting & NBO ing LOAD#72/14/99 B. Wester RECEIVED AND BAKED 0990029 5/N 011 IN LOAD # 70 B. RIVERA 1.4.00 |
| RECEILUED AND BAKED D990029 SWOII IN LOAD # 70 B. RIVERA 1.4.00 |

X-POP3-Rcpt: bweaver@apex

Date: Thu, 22 Jul 1999 12:12:31 -0700

From: Dennis Coyne < coyne@ligo.caltech.edu>

Organization: Caltech/LIGO

X-Mailer: Mozilla 3.01Gold (Win95; I)

To: Betsy Weaver < weaver b@ligo.caltech.edu> CC: Stan Whitcomb <stan@acrux.ligo.caltech.edu>, Mike Smith <smith@acrux.ligo.caltech.edu>. Bartie Rivera <rivera b@ligo-wa.caltech.edu>

Subject: Re: cleaning

You should clean as follows (E960022-05 except since the parts are too large to ultrasonically clean, I've tailored the cleaning):

- 1) clean with Liquinox first (solution per E960022-05) and using a rubbing/scrubbing action (i.e. not just rinsing the liquinox over the surfaces). All holes must be cleaned with a brush (stainless steel, phosphor-bronze preferred, but nylon is acceptable). It is ESSENTIAL that the liquinox NOT dry before being rinsed with DI water.
- Thoroughly rinse with DI water. All surfaces and holes must be rinsed. THOROUGHLY.
- 3) Rinse & rub (with gloved hand only) all surfaces with either methanol or isopropal alcohol. Squirt the solvent into all holes.
- 4) Blow dry with clean, filtered air or N2, or allow to dry on a clean bench. Do not leave exposed for longer than about 15 minutes, before covering with UHV foil.

With regard to cleaning the lens, please see Stan for a confirmation, but I believe the rule that we operate under is that if all surfaces are polished, then an optics cleaning and wetting test is adequate and no baking is required. However, if the sides of the optic are not polished (as I suspect is the case for the ETM optics), then it should be cleaned and baked and re-cleaned. However, please confirm this with Stan and he may grant a waiver if he examines the surface condition of the optics. Dennis

Betsy Weaver wrote:

> Hi Dennis-

> Two cleaning questions for you:

We just received the aluminum load (COS) from the etching company.

> How should we clean them here, before baking them? (They are

48

MBO LOAD

Dennis Coyne, 12:12 PM 7/22/99 -0700, Re: cleaning

- > obviously too large to put in the ultrasonic cleaner...)
- >
- > 2. Mike has one large and two small lenses that are going to be
- > used in the ETM Telescope Assembly. If they wet well during cleaning,
- > do they really need to be baked? A while ago, Stan told me that the
- > small steering mirrors for IO and COS did not need to be baked, as the oven
- > would just make them dirtier, because they wetted so well during cleaning.
- > Is this the same for the lenses? If they do need to be baked, can I put
- > them in
- > the next load with the one Large Optic?
- >
- > Thanks-
- > Betsy

Dennis Coyne (Detector Installation Manager) LIGO Laboratory, Caltech, Physics Department 626.395.2034 @CIT / 225.686.3168 @Livingston / 509.372.8166 @Hanford cell 626.695.8350