

Status of High-Power Laser Development at Stanford

Todd S. Rutherford* , Shailendhar Saraf, Karel Urbanek,
Justin Mansell, Eric K. Gustafson, and Robert L. Byer
E. L. Ginzton Laboratory, Stanford University

LIGO Science Collaboration Meeting
Hanford Site, August 15-17 2000




Outline

- Review
- Progress since last LSC
 - Preliminary results on wavefront distortion
 - Installation of new diodes
- (Near) Future Work




Configuration

- Two zig-zag slab amplifiers
 - Brewster ends
 - 3:1 aspect ratio (width/thickness)
- About 900 W total pump power
- Use Lightwave 10 W as master oscillator
- Goal: 100 W, low M^2

The Single -Triple Pass Amplifier





The Double-Triple Pass Amplifier



Unsaturated Amplifier


Unsaturated Amplifier

$$P_{\text{in}} = 300 \text{ mW}$$




Slab Wavefront

- Measured with Shack-Hartmann wavefront sensor
- Dominant distortion is tilt
- More detailed analysis in progress



Tilt Removed



Laser diode upgrade

Laser diodes

- Manufacturer: Coherent
- 30 W each
- 808 nm
- Fiber coupled
 - 400 μm core
 - 0.2 NA
- 24 units
- 720 W total




Power Supplies

- Manufacturer: Newport
- 100 A, 14 V
 - Drive 6 bars in series
- Temperature Control
 - PID controllers
 - TEC drivers
- GPIB/RS-232
- Fault protection

Installation Complete




- Labview control of diode:
 - Current
 - Voltage
 - Temperature
- Interlocks



Power Scaling Challenges

- Beam Quality
 - Difficult to model
 - Distortions depend critically on slab boundary conditions
- RF Intensity noise
 - High circulating power in PMC(s)
 - Requirements eased with DC readout
- Parasitic Oscillations
- Depolarization
 - Near edges only
- Temperature detuning

Depolarization



- Stress near edge of slab is not completely aligned with polarization
- Sensitive to fiber position and distribution
- 300 W pump \sim 15 % stress fracture limit

Future Work

- Calibrate Diodes (1 week)
 - Temperature for optimum absorption
 - Power vs Current curves
- Assemble second amplifier head (2 days)
 - Machining finished
- Mount fiber clamp to second head (1 week)
- Power tests of second head (2 weeks)
- Begin amplification experiments