

DRMI Noise Budget Overview

Denis Martynov for the LLO commissioning team


December 4, 2013

DRMI Optical Configuration

EOM Modulation:
 $F_1 = 9099385 \text{ Hz}$
 $\Gamma_1 = 0.26$
 $F_2 = 45496925 \text{ Hz}$
 $\Gamma_2 = 0.3$



Laser
Pin = 10W



PRM

PR2

Seismic isolation status:

ISI: HAMs run level 2 isolation loops, BSCs run level 3 on ST1 blending CPS/T240/L4C and level 1 for X, Y and RZ on ST2

HEPI: HAMs are locked, BSCs run position sensor loops

Angular controls run 3 WFS loops in pitch and yaw + PR3 cage servo

RF sensors: REFL_A_9I,
REFL_B_9I, AS_45Q

Actuators:

PR2 (UGF=5Hz),
BS (UGF=2Hz)

DRMI Sideband Sensing:

REFL9I -> PRCL

REFL9Q -> MICH

REFL45I -> SRCL

PRMI Carrier Sensing:

REFL9I -> PRCL


OMC DC -> MICH

Actuation:


PRCL -> PRM, PR2 (UGF=100Hz)

MICH -> BS (UGF=10Hz)

SRCL -> SRM, SR2 (UGF=30Hz)




MICH Noise Budget (input power=5W, offset=1.5nm)



PRCL Noise Budget (input power=1W, PRC build up=30)

DRMI Sideband Configuration



SRCL Noise Budget (input power=1W, PRC build up=30)

