

FEP Hookup Wire

Stranded Bare Copper

Temperature: -80 C to 200 C. Voltage Rating: 150 volts.

Wire Series ▲	Cable Series.	AWG Size	Conductor Circ. Mils	Strand Constr.	Nom. Wall Thickness FEP	Nominal Overall Diameter	OHMS Per Foot
CZ 1103	(CZ 1103-1)	40	10	10/50	.003-004	.011	1.080
CZ 1187	(CZ 1223-1)	38	15	15/50	.003-004	.012	.720
CZ 1174	(CZ 1215-1)	36	25	25/50	.003-004	.013	.430
CZ 1321	(CZ 1324-1)	34	40	40/50	.003-004	.014	.270
CZ 1111	(CZ 1111-1)	33	49	50/50	.003-004	.015	.220
CZ 1322	(CZ 1325-1)	32	64	64/50	.003-004	.016	.170
CZ 1209	(CZ 1209-1)	31	74	75/50	.003-004	.019	.150
CZ 1320	(CZ 1323-1)	30	99	40/46	.003-004	.022	.110
CZ 1104	(CZ 1104-1)	29	126	51/46	.003-004	.023	.085
CZ 1105	(CZ 1105-1)	28	161	65/46	.003-004	.024	.06